



Rear-Discharge Mixers | The Bridgemax Specifications

ROADBUILDING



REAR-DISCHARGE MIXERS

New from Terex: The premier name in front-discharge mixers is now the premier name in rear-discharge mixers, too. That makes us The Total Solution™ for any concrete placement need. Front or rear, you get everything Terex has come to be known for: top quality ... the wisdom of experience ... fast, responsive service, before and after the sale ... readily available parts ... and delivery you can count on. So, what's your preference? Front-discharge, rear-discharge—or both? Any way you look at it, Terex is looking mighty good for your bottom line.

DETAILS. DETAILS.



In-Cab Controls



Water Tank



Hydraulic Tank



Fold-Down Ladder



LED Lighting



Discharge Chute

STANDARDS & OPTIONS

MIXER DRUM—TMMB Certified

Size:	10, 10½ or 11 yd³
Material:	AR plate, ⅜ in skin and ¼ in fins & flights
Optional:	AR plate, ¼ in skin and ¼ in fins & flights lined with rebar 400 Brinell, ⅜ in skin and AR ⅜ in fins & flights, rebar available
Drum Opening:	46 in, standard
Optional:	42 in
Hydrostatics:	Eaton® 5.4 in³ displacement pump with integrated remote electronic valves Eaton 5.4 in³ displacement motor
Drum Drive:	ZF P 7300
Optional:	PK 7500
Hopper:	⅜ in AR plate material 42 in x 28 in opening
Optional:	Air flip-up

MIXER MOUNT

Bridgemax:	Welded frame reinforcement. Pedestals spring-loaded and hard-fastened with Grade 8 bolts
------------	---

WATER TANK

Available:	75 gal, 120 gal, 150 gal or 200 gal @ 120 psi aluminum or steel tank 20 gal plasticizer
------------	---

DISCHARGE CHUTE

Standard:	Manually rotated, hydraulically lifted-and-lowered 34 in chute with manual flip
Optional:	Hydraulic flip chute, Air chute brake

BRIDGEMAX

6 in hydraulic cylinder with integral nitrogen-charged
accumulator stem attached with 2¼ in bearings
Trailer weldment—Fabricated ⅜ in grade 80 material
Trailer axle—13,000 lb capacity steerable axle and
self-centering shock assemblies
Auto-up in reverse with built-in safety features and alarms

MISCELLANEOUS

Optional:	Work lights Tow bar Slump meter in cab or mixer mount Constant speed controls Drum spray bar Urethane hopper & chute liners
-----------	--



7727 Freedom Way, Fort Wayne, IN 46818 • Ph: 800/678-5961 Fax: 260/969-4528 • www.terexrb.com

©Copyright 2007 Terex Corporation. All rights reserved. Terex® is a registered trademark of Terex Corporation in the United States of America and many other countries. Materials and specifications subject to change without notification.

 **TEREX**
Roadbuilding